

Fit-PC2 sammenligningsskema

Model	fit-PC2 Value	fit-PC2 diskless	fit-PC2 Linux	fit-PC2 XP	fit-PC2 Win7
CPU	Intel Atom Z510 1.1GHz	Intel Atom Z530 1.6GHz	Intel Atom Z530 1.6GHz	Intel Atom Z530 1.6GHz	Intel Atom Z530 1.6GHz
Chipset	US15W SCH	US15W SCH	US15W SCH	US15W SCH	US15W SCH
Memory	1GB DDR2 Ram	1GB DDR2 Ram	1GB DDR2 Ram	1GB DDR2 Ram	1GB DDR2 Ram
Software					
OS	-	-	Ubuntu Linux	Windows XP	Windows 7 Professional
Network					
LAN	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet
WLAN	-	802.11b/g	802.11b/g	802.11b/g	802.11b/g
Wake-on-Lan	-	-	-	-	-
Graphics					
Chipset	Intel GMA500	Intel GMA500	Intel GMA500	Intel GMA500	Intel GMA500
Resolution	Up to 1920x1200	Up to 1920x1200	Up to 1920x1200	Up to 1920x1200	Up to 1920x1200
Storage					
SATA	Bay for 2,5" SATA	Bay for 2,5" SATA	Bay for 2,5" SATA	Bay for 2,5" SATA	Bay for 2,5" SATA
SD	MiniSD socket	MiniSD socket	MiniSD socket	MiniSD socket	MiniSD socket
HDD	-	-	160 GB SATA	160 GB SATA	160 GB SATA
Flash	-	-	-	-	-
Power					
Adaptor	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz
Input	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)
Consumption	5W	5W	5W	5W	5W
Auto-ON	-	Optional	Optional	Optional	Optional
Physics					
Dimensions	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc
Case	Fanless aluminium case	Fanless aluminium case	Fanless aluminium case	Fanless aluminium case	Fanless aluminium case
I/O					
Display	DVI / HDMI connector	DVI / HDMI connector	DVI / HDMI connector	DVI / HDMI connector	DVI / HDMI connector
Audio	HD Line-out 2.0, line-in, mic-in	HD Line-out 2.0, line-in, mic-in	HD Line-out 2.0, line-in, mic-in	HD Line-out 2.0, line-in, mic-in	HD Line-out 2.0, line-in, mic-in
LAN	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet	1 x Gigabit Ethernet
USB	4 x USB, 2 x Mini-USB 2.0	4 x USB, 2 x Mini-USB 2.0	4 x USB, 2 x Mini-USB 2.0	4 x USB, 2 x Mini-USB 2.0	4 x USB, 2 x Mini-USB 2.0
Infrared	IR Reciever	IR Reciever	IR Reciever	IR Reciever	IR Reciever
Serial	-	-	-	-	-

Linuxshoppen er dansk distributør og forhandler af fit-PC2 og fit-PC2i - Læs mere og bestil direkte på:

www.linuxshoppen.dk/fit-pc

Fit-PC2i sammenligningsskema

Model	fit-PC2i Value	fit-PC2i diskless	fit-PC2i Linux	fit-PC2i Linux	Fit-PC2i Win7
CPU	Intel Atom Z510 1.1GHz	Intel Atom Z530 1.6GHz	Intel Atom Z530 1.6GHz	Intel Atom Z530 1.6GHz	Intel Atom Z530 1.6GHz
Chipset	US15W SCH	US15W SCH	US15W SCH	US15W SCH	US15W SCH
Memory	1GB DDR2 Ram	1GB DDR2 Ram	1GB DDR2 Ram	2GB DDR2 Ram	2GB DDR2 Ram
Software					
OS	-	-	Ubuntu Linux	Ubuntu Linux	Windows 7 Professional
Network					
LAN	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet
WLAN	-	802.11b/g	802.11b/g	802.11b/g	802.11b/g
Wake-on-Lan	Supported	Supported	Supported	Supported	Supported
Graphics					
Chipset	Intel GMA500	Intel GMA500	Intel GMA500	Intel GMA500	Intel GMA500
Resolution	Up to 1920x1200	Up to 1920x1200	Up to 1920x1200	Up to 1920x1200	Up to 1920x1200
Storage					
SATA	Bay for 2,5" SATA	Bay for 2,5" SATA	Bay for 2,5" SATA	Bay for 2,5" SATA	Bay for 2,5" SATA
SD	MiniSD socket	MiniSD socket	MiniSD socket	MiniSD socket	MiniSD socket
HDD	-	-	160 GB SATA	160 GB SATA	160 GB SATA
Flash	-	-	-	4 GB On-board	4 GB On-board
Power					
Adaptor	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz	AC 100-240V 50-60Hz
Input	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)	DC 12V power supply (9-15V tolerant)
Consumption	5W	5W	5W	5W	5W
Auto-ON	Yes	Yes	Yes	Yes	Yes
Physics					
Dimensions	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc	H27mm x W115mm x L 101mm - Volume 313cc
Case	Fanless aluminium case	Fanless aluminium case	Fanless aluminium case	Fanless aluminium case	Fanless aluminium case
I/O					
Display	DVI / HDMI connector	DVI / HDMI connector	DVI / HDMI connector	DVI / HDMI connector	DVI / HDMI connector
Audio	S/PDIF 5.1 via COAX, line-out, line-in, mic-in	S/PDIF 5.1 via COAX, line-out, line-in, mic-in	S/PDIF 5.1 via COAX, line-out, line-in, mic-in	S/PDIF 5.1 via COAX, line-out, line-in, mic-in	S/PDIF 5.1 via COAX, line-out, line-in, mic-in
LAN	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet	2 x Gigabit Ethernet
USB	2 x USB, 2 x Mini-USB 2.0	2 x USB, 2 x Mini-USB 2.0	2 x USB, 2 x Mini-USB 2.0	2 x USB, 2 x Mini-USB 2.0	2 x USB, 2 x Mini-USB 2.0
Infrared	-	-	-	-	-
Serial	RS232 full UART	RS232 full UART	RS232 full UART	RS232 full UART	RS232 full UART

Linuxshoppen er dansk distributør og forhandler af fit-PC2 og fit-PC2i - Læs mere og bestil direkte på:

www.linuxshoppen.dk/fit-pc